

LED PÁS CV ERALED - SÉRIA RGBW 4in1

LED pás konštantného napätia SMD5050 - RGBW IP67



Model

ERA5050-4WK60-RGBWW

ERA5050-4WK60-RGBNW

ERA5050-4WK60-RGBCW

R	G	B	3000K
R	G	B	4000K
R	G	B	6000K

ELEKTRO PARAMETER	24VDC		
	18W/m		
FARBA CCT	RGBW - 480nm, 3000K - 580nm		
	R - 630nm, G - 520nm, B - 460nm		
LED INFO	SMD5050 30z		
	60LED/m		
SVETELNÝ TOK	Red	4,5W/m	120 lm/m
	Green	4,5W/m	322 lm/m
	Blue	4,5W/m	97 lm/m
	3000K	4,5W/m	540 lm/m
	RGBW	18,0W/m	1070 lm/m
TEPLOTA	Pracovná - 20° ~ + 45°C		
	Max < 65°C		
OVLÁDANIE	RGBW, DALI, DMX512		
	RF-RGBW		
VYŽAROVACÍ UHOL	120°		
KRYTIE	IP67		
	vol. IP20		
ROZMERY - IP67	Šírka	14 mm	
	Hrúbka	5 mm	
	Delenie	100 mm	
	Balenie	5 m	
OSTATNÉ	CE, RoHS, UL, FCC, EN-C		
	Záruka 3 roky		

